



PC Board Layout
Component Side Shown

NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE ∅0.46mm.
- 3.PLATING :GOLD PLATING OVER NICKEL.

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :1.5 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50Hz. 1MIN.

MECHANICAL:

- 1.DURRABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1 LB MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40℃~+85℃
- 2. OPERATION : 0℃ TO 70℃.

<p>APPD. 核准 Betty</p>			TOLERANCE 容許公差		<p>PART NAME TOP ENTRY PCB JACK 6P6C WITH PANEL STOP HALF ROUND FOOT BLACK COLOR ROHS</p>
			SCALE 比例	參考	
<p>DWG. 製圖 Betty</p>		<p>UNIT 單位 M M</p>	SIZE. 紙張尺寸		<p>PART NO. F66</p>
			ANGLE 角度	± 3°	
<p>DATE 制表日 2012/12/10</p>		<p>PAGE 張數 1 OF 1</p>	<p>REV. 版次 A</p>		